

Service Schedule

ABI Force Z-23

Daily

Check Engine Oil	SAE 30 or 5w-40 Full Synth Engine Oil
Check Hydraulic Oil	SAE 5w-40 Full Synth Only
Check Fuel	87 Octane E10 or less Regular Gasoline
Check Tire Pressures	Front 25 psi Rear 20 psi

After First 25 Hours

Change Engine Oil and Filter	Kohler part 52 050 02-S filter
Check Lugnut torque	90-120 ft lbs

Every 50 Hours of Operation

Blow out engine compartment and cooling fins	
Grease pivot points and front wheels	
Inspect Outer Air filter element	Kohler part 25 083 01-S
Inspect for loose fasteners	
Inspect hydraulics for leaks and moving hoses for damage	

After First 100 Hours

Change Hydraulic Oil and Filter	5w-40 Full Synth Oil	Lenz CP-752-10 Filter
Check Lugnut Torque	90-120 ft lbs	

Every 100 Hours of Operation

Change Hydraulic Oil and Filter	Kohler part 52 050 02-S filter
Check Lugnut Torque	90-120 ft lbs

Every 200 Hours of Operation

Replace Fuel Filter (EFI specific)	Kohler part 25 050 42-S Only
------------------------------------	------------------------------

Every 300 Hours of Operation

Replace Inner Air Filter element	Kohler part 25 083 04-S
----------------------------------	-------------------------

Every 500 Hours of Operation

Change Hydraulic Oil and Filter	5w-40 Full Synth Oil	Lenz CP-752-10 Filter
Lubricate Pump Driveshaft	Kohler part 25 357 12-S only	
Replace Spark Plugs and set gap	Kohler part 25 132 12-S at 0.03" gap	