Service Schedule **ABI Force Z-23**

Daily

Check Engine Oil Check Hydraulic Oil Check Fuel **Check Tire Pressures** Blow out engine compartment and cooling fans Check attachment wear parts Inspect Outer Air filter element

After First 25 Hours

Change Engine Oil and Filter Check Lugnut torque

Every 50 Hours of Operation

Blow out engine compartment and cooling fins Grease pivot points and front wheels Inspect Outer Air filter element Inspect for loose fasteners Inspect hydraulics for leaks and moving hoses for damage

After First 100 Hours

Change Hydraulic Oil and Filter **Check Lugnut Torque** Lubricate Pump Driveshaft

Every 100 Hours of Operation

Change Hydraulic Oil and Filter **Check Lugnut Torque**

Every 200 Hours of Operation

Replace Fuel Filter (EFI specific)

After First 250 Hours

Lubricate Pump Driveshaft

Every 300 Hours of Operation

Replace Inner Air Filter element

Every 500 Hours of Operation

Change Hydraulic Oil and Filter Lubricate Pump Driveshaft Replace Spark Plugs and set gap

SAE 30 or 5w-40 Full Synth Engine Oil SAE 5w-40 Full Synth Only 87 Octane E10 or less Regular Gasoline Front 25 psi Rear 20 psi

Kohler part 25 083 01-S

Kohler part 52 050 02-S filter 90-120 ft lbs

Kohler part 25 083 01-S

5w-40 Full Synth Oil 90-120 ft lbs

Kohler part 52 050 02-S filter 90-120 ft lbs

Kohler part 25 050 42-S Only

Kohler part 25 357 12-S only

Kohler part 25 083 04-S

5w-40 Full Synth Oil Kohler part 25 357 12-S only Kohler part 25 132 12-S at 0.03" gap

Lenz CP-752-10 Filter

Kohler part 25 357 12-S only

Lenz CP-752-10 Filter